

Installation Ready!



TMA-54ZBT

1920W CE APPROVED
TOTAL SYSTEM - PEAK POWER



5 Channel Mixer / 4 Zones

Frequency Response: 60-17KHz (-3dB)
Treble: 10dB at 10KHz / Bass: 10dB at 100Hz

Priority for Mic-1

Output Constant Voltage: 25V, 70V & 100V

8 Volume Controls for: Ch1-5, Tel. Paging, Monitor & Phone



TMA-54ZBT

Inputs Sensitivity	Ch1- 4: Mic/Phantom: -50dBV; Line: -10dBV balance / CH5: -10dBV unbal. / Telephone paging: -10dBV
Frequency response	60-17000Hz (-3dB)
Tone control	Treble: 10dB at 10KHz / Bass: 10dB at 100Hz
T.H.D.	<1%
S/N ratio	Mic. >65dB / Line >75dB / Tel. >65dB
Priority for Mic-1	mute CH2-CH5
Outputs impedance	4 Ohm, 8 Ohm
Output constant voltage	25V, 70V, 100V
Power Rating	960W PROGRAM / 1920W PEAK
Monitor output	1W RMS
Phone output	1V (47 Ohm)
Line out	2.0V (BAL)
Monitor Line out	1V (600 Ohm)
Controls	5 Gain controls for Ch1-5 / 8 Volume controls for Ch1-5, tel. paging, monitor, phone / 4 Master volume control / 5 Treble controls / 5 Bass controls / 4 Zone select switch for each channel / 4 Zone monitor select switch / 5 mute controls / 1 AC select switch / 1 Bluetooth PAIR Switch
Indicate LED	5VU meters (LED type) / 1 Power indicator / 5 Mute indicators / 1 Bluetooth PAIR indicators
Dimensions (HxWxD)	133 x 483 x 395 mm / 5.24" x 19.02" x 15.55"
Power Supply	110-120V~ 60Hz or 220-240V~50/60Hz Switch mode



WWW.SISTEMAMT.IT



supporto@musictechnology.it



+39 071 7926753