

Active PA System

# EVENT2K SYSTEM



**4000W** **CE**  
4 OHM PEAK POWER - TOTAL SYSTEM APPROVED

12 x 3.5" HD Speakers

15" Active Subwoofer

12 x 3.5" HD Speakers

15" Active Subwoofer

Easy to Set Up and Transport!

180°  
Dispersion

**MAXHED**  
POWER MODULE Optimum Headroom & SPL

**Hi-Def**  
COMPONENTS



Download the FREE  
App from App Store  
to Control!



[WWW.SISTEMAMT.IT](http://WWW.SISTEMAMT.IT)



[supporto@musictechnology.it](mailto:supporto@musictechnology.it)



+39 071 7926753

# EVENT2K Technical Specifications



## EVENT 2K SYSTEM

Frequency Response	40Hz - 20KHz (-10dB)
Total Amplifier Power	1000W Continuous / 2000W Program / 4000W Peak Class-D @ 4 Ohm
Maximum SPL@1M	128dB
Crossover Frequency	220Hz
Dispersion (-6dB)	120° Horizontal
Dimensions (WxHxD)	440 x 2015 x 640 mm / 17.32" x 79.33" x 25.20"
Net Weight	37.81 Kg / 83.35 lbs

## Subwoofer

System Type	15" Active Subwoofer Speaker Cabinet
Frequency Response (-6dB)	40Hz - 210Hz
Total Amplifier Power	1000W Continuous / 2000W Program / 4000W Peak Class-D @ 4 Ohm
Amplifier, Subwoofer	500W Continuous / 1000W Program / 2000W Peak Class-D @ 4 Ohm
Amplifier, Satellite	500W Continuous / 1000W Program / 2000W Peak Class-D @ 4 Ohm
DSP Presets Modes	LIVE / Music / FLAT / SPEECH / DJ
Electronic Protections	Overheat Protection / Short Circuit Protection / Digital Compressor
Cooling	Temperature-controlled fan
Connections	Input: 4 x Combo-XLR & 1/4", 1 x RCA In L&R, 1 x 3.5 Stereo Jack, Output: 1 x XLR Thru & Mixout
External Controls	Volume Control / Switch for Input sens / Switch for mode selector / Power ON with Green LED / Limiter with Red LED / Ground Lift / OLED DSP Display and Control / IP Control / MP3 and BT (optional)
Power Supply	115V/230V ~50/60Hz Switch mode
Enclosure Construction	Plywood Cabinet, Resistant Black Paint, Metal Grille with Foam, Rubber Feet, Integrated side handles
Mounting	Smart Mounting and Connection
Dimensions (WxHxD)	440 x 521 x 640 mm / 17.32" x 20.49" x 25.20"
Net Weight	26.1 Kg / 57.54 lbs

## Pole

Enclosure Construction	15" Active Aluminium Cabinet, Metal Grille, Resistant Paint
Connector	2 x Electronic Adapter - 1 x Input Connector for Sub & Another with Input Connector for Satellite
Dimensions (WxHxD)	1135 x 354 mm / 13.94" x 4.43"
Net Weight	1.36 Kg / 3.0 lbs

## Satellite

System Type	6 x 3.5" Passive Speaker System
Output Power	180W Continuous, 360W Program, 720W Peak
Sensitivity (1W/1M)	96dB
Frequency Response (-6dB)	150Hz-20KHz
Impedance	16 Ohm
Transducer Low	3.5" Woofer, 1" Voice Coil
Rotation	180 Degree Mechanical Adjustment
Enclosure Construction	Aluminium Cabinet, Metal Grille, Resistant Paint
Connector	2 x Electronic Adapter - 1 x Input Connector for AX Pole & Another with Input Connector for AXV62TP
Dimensions (WxHxD)	113 x 610 mm / 4.43" x 24.0"
Net Weight	5.2 Kg / 11.46 lbs

## SAT-TP

System Type	6 x 3.5" Passive 6 x 3.5" Passive Speaker System
Output Power	180W Continuous, 360W Program, 720W Peak
Sensitivity (1W/1M)	96dB
Frequency Response (-6dB)	150Hz-20KHz
Impedance	16 Ohm
Transducer Low	3.5" Woofer, 1" Voice Coil
Rotation	180 Degree Mechanical Adjustment
Enclosure Construction	Aluminium Cabinet, Metal Grille, Resistant Paint
Connector	2 Pin smart connection
Dimensions (WxHxD)	113 x 583 mm / 4.43" x 22.96"
Net Weight	5.15 Kg / 11.35 lbs

Subwoofer rear view



4 Ch Mixer  
DSP  
OLED Display

