

Active PA System



EVENT4K SYSTEM

8000W **CE**
4 OHM PEAK POWER - TOTAL SYSTEM APPROVED

24 x 3.5" HD Speakers

24 x 3.5" HD Speakers

2 x 15" Active
Subwoofers

2 x 15" Active
Subwoofers

Easy to Set Up and Transport!

130°
Dispersion

MAX HED
POWER MODULE Optimum Headroom & SPL



Download the FREE
App from App Store
to Control!



WWW.SISTEMAMT.IT



supporto@musictechnology.it



+39 071 7926753

EVENT4K Technical Specifications



EVENT 4K SYSTEM

Frequency Response	35Hz - 20KHz (-10dB)
Total Amplifier Power	2000W Continuous / 4000W Program / 8000W Peak / Class-D @ 4 Ohm
Maximum SPL@1M	134dB
Crossover Frequency	200Hz
Dispersion (-6dB)	130° Horizontal
Dimensions (WxHxD)	460 x 2010 x 676 mm / 18.11" x 79.13" x 26.6"
Net Weight	50.15 Kg / 110.56 lbs

Subwoofer

System Type	2 x 15" Active Subwoofer Speaker Cabinet
Frequency Response	35Hz - 180Hz (-6dB)
Total Amplifier Power	2000W Continuous / 4000W Program / 8000W Peak / Class-D @ 4 Ohm
Amplifier, Subwoofer	1000W Continuous / 2000W Program / 4000W Peak / Class-D @ 4 Ohm
Amplifier, Satellite	1000W Continuous / 2000W Program / 4000W Peak / Class-D @ 4 Ohm
DSP Presets Modes	LIVE / Music / SPEECH / DJ
Electronic Protections	Overheat Protection / Short Circuit Protection / Digital Compressor
Cooling	Temperature-controlled fan
Connections	Input: 4 x Combo-XLR & 1/4", 1 x RCA In L & R, 1 x 3.5 Stereo Jack, Output: 1 x XLR Thru & Mixout
External Controls	Volume Control / Switch for Input sens. / Switch for mode selector / Power ON with Green LED / Limiter with Red LED / Ground Lift / OLED DSP Display and Control / IP Control / MP3 and BT module (optional)
Power Supply	115V/230V ~50/60Hz Switch mode
Enclosure Construction	Plywood Cabinet, Resistant Black Paint, Metal Grille with Foam, Wheels, Integrated side handles
Mounting	Smart Mounting and Connection
Dimensions (WxHxD)	460 x 830 x 676 mm / 18.11" x 32.67" x 26.6"
Net Weight	40.47 Kg / 89.22 lbs

Satellite

System Type	24 x 3" Passive Speaker System
Output Power	480W Continuous, 960W Program, 1920W Peak
Sensitivity (1W/1M)	99dB
Frequency Response	150Hz-20KHz (-6dB)
Impedance	4 ohms
Transducer Low	3" Neodymium Fullrange Speaker, 0.8" Voice Coil
Enclosure Construction	Aluminium Cabinet, Metal Grille, Resistant Paint
Connector	2 Pin smart connection
Dimensions (WxHxD)	167 x 1170 mm / 6.57" x 46.06"
Net Weight	9.7 Kg / 21.38 lbs

EVENT4K
rear & side view



Subwoofer rear view



4 Ch Mixer
DSP
OLED Display

www.toppopro.com



WWW.SISTEMAMT.IT



supporto@musictechnology.it



+39 071 7926753