

HD Active Speaker with DSP



X Series



1600W **126dB** **CE**
TOTAL SYSTEM - PEAK POWER APPROVED

1" Neodymium Driver



Download the free App from App Store to control!

DSP Enhanced Bass Response

Your Own Sound Calibration!



NEODYMIUM ND DRIVER



MAXHEB
POWER MODULE Optimum Headroom & SPL

Hi-Def
COMPONENTS

Rigging
READY!

X8A	X10A	X12A	X15A	X CS12A	X CS15A
1.5"	1.5"	2"	2"	2"	2"
VOICE COIL	VOICE COIL	VOICE COIL	VOICE COIL	VOICE COIL	VOICE COIL



WWW.SISTEMAMT.IT



supporto@musictechnology.it



+39 071 7926753

X Series Active Technical Specifications



	X8A	X10A	X12A	X15A
System Type	2-Way Active Vented Speaker			
Transducer Low	8" Woofer, 1.5" voice coil	10" Woofer, 1.5" voice coil	12" Woofer, 2" voice coil	15" Woofer, 2" voice coil
Transducer Driver	1" Ferrite Twitter, 1" Voice Coil		1" NEO Driver, 1" Voice Coil	
Horn Coverage H° x V°	90°H x 60°V			
Frequency Response (-6dB)	68Hz-20KHz	65Hz-20KHz	60Hz-20KHz	55Hz-20KHz
Crossover Frequency	2000 Hz	1900 Hz	2100 Hz	2100 Hz
Max SPL	113dB at 1m	116dB at 1M	118dB Max.	119dB Max.
Power Rating	240W PROGRAM 480W PEAK	240W PROGRAM 480W PEAK	400W PROGRAM 800W PEAK	400W PROGRAM 800W PEAK
Connector	Line In & Link With XLR			
External Controls	Volume Control / Power ON with Green LED / Contour / MIC & Line Switch / Clip Limiter with Red LED / Ground Lift			
Electronic Protections	Thermal / Overload / Analog limiter / Compressor			
Power Supply	110V-120V / 50-60Hz or 220V-240V / 50-60Hz			
Enclosure Construction	Plastic cabinet, Trapezoidal & Monitor shape, Metal grille, Rubber foot, 1 x Handle-On Top			
Mounting	36mm standard pole-mount / M10 x 4pcs Flying Points (Optional)			
Dimensions (HxWxD)	346 x 321 x 478 mm 13.62" x 12.64" x 18.82"	361 x 341 x 578 mm 14.21" x 13.43" x 22.76"	458 x 411 x 683 mm 18.03" x 16.18" x 26.89"	468 x 488 x 708 mm 18.43" x 19.21" x 27.87"
Net Weight	5.4 Kg / 11.91 lbs	6.92 Kg / 15.26 lbs	13.2 Kg / 29.1 lbs	14.5 Kg / 32 lbs
Volume	1.87 CFT	2.25 CFT	4.54CFT	5.47CFT

X Series Also available in PASSIVE version

	X CS12A	X CS15A
System Type	2-Way Active Vented Speaker / Bi-Amp. With DSP processor	
Transducer Low	12" Woofer, 2" voice coil	15" Woofer, 2" voice coil
Transducer Driver	1" Neodymium Driver, 1" Voice Coil	
Horn Coverage H° x V°	90°H x 60°V	
Frequency Response	50Hz-20KHz (-6dB)	45Hz-20KHz (-6dB)
Crossover Frequency	1.6KHz - DSP Processor	
Max SPL	125dB Max.	126dB Max.
AMP Power Output	400W Continuous (LF-Class D 350W, HF-Class AB 65W), 1600W Peak	
Connector	Line/Mic With Combo & Link With XLR	
External Controls	Volume Control / Lin & Mic Switch / Preset Switch / Power on with Green LED / Clip Limiter with Red LED / Ground Lift	
Digital Presets	FLAT - MUSIC - USER	
Electronic Protections	Thermal / Overload / Digital Limiter / Compressor	
Power Supply	110V-120V~50/60Hz or 220V-240V~50/60Hz Switch mode	
Enclosure Construction	Plastic cabinet, Trapezoidal & Monitor Shape, Metal Grille, Rubber Feet, 3 x Handles (Top and sides)	
Mounting	36mm standard pole-mount	
Dimensions (HxWxD)	458 x 411 x 683 mm / 18.03" x 16.18" x 26.89"	468 x 488 x 708 mm / 18.43" x 19.21" x 27.87"
Net Weight	14.6 Kg / 32.19 lbs	14.7 Kg / 32.41 lbs
Volume	4.54 CFT	5.47 CFT

www.toppopro.com



WWW.SISTEMAMT.IT



supporto@musictechnology.it



+39 071 7926753