



KS CMA & TPS MA Series



1600W 129dB

TOTAL SYSTEM - PROGRAM POWER



1.75" HD Driver

3 User-Selectable Settings:
Vocal Focus 1 / 2 & Satellite FOH

Both monitors are fully
adjustable! 45° Angle



KS 12CMA



KS 15CMA



830W 121dB

TOTAL SYSTEM - PROGRAM POWER



1" HD Driver

2 User-Selectable Settings:
Monitor & Satellite FOH



TPS 12MA



TPS 15MA



KS CMA & TPS MA Series Active Technical Specifications



	KS 12CMA	KS 15CMA
System Type	2-Way Active Monitor with DSP	
Transducer Low	12" Woofer, 3" Voice Coil	15" Woofer, 3" Voice Coil
Transducer Driver	1" Compression Driver, 1.75" Voice Coil	
Nominal Coverage (HV)	60° x 40° (-6dB)	
Frequency Response	60Hz - 20KHz (-6dB)	55Hz - 20KHz (-6dB)
Crossover Frequency	At 1.5KHz with 24dB filter slope, Linkwitz-Riley Type	
Max SPL	128dB Max.	129dB Max.
Power Rating	1600W PROGRAM - 3200W PEAK	
Input Connector	Line/Mic - Combo/Link - XLR	
Line Input	Combo Connector 0dBu	
DSP Presets	VOCAL1 / FLAT / VOCAL2	
External Controls	Volume Control / Power ON with Green LED / Clip Limiter with Red LED / Ground Lift / Switch for Input Sens	
Electronic Protections	Thermal / Convection-Fan / Overload / Digital Limiter / Compressor	
Power Supply	115V 60Hz / 230V 50Hz Switch mode	
Enclosure Construction	Trapezoidal, Plywood cabinet, resistant black paint, metal grille with black foam, rubber feet	
Monitor angle	Adjustable (20°, 25°, 30°, 35°, 40°)	
Dimensions (HxWxD)	292 x 470 x 570 mm / 11.5" x 18.5" x 22.44"	307 x 510 x 570 mm / 12.09" x 20.08" x 22.44"

	TPS10MA	TPS12MA
System Type	2-Way Bi-Amp Active Monitor Speaker, with DSP	
Power Rating	830W PROGRAM / 1660W PEAK	
Frequency Response	68Hz - 20KHz (-6dB)	60Hz - 20KHz (-6dB)
Speaker Sensitivity (1m)	94dB / 120dB Max.	95dB / 121dB Max.
Low Frequency	10" Woofer / 2" Voice Coil, with ventilation	12" Woofer / 2" Voice Coil, with ventilation
High Frequency	1" Driver / 1" Voice Coil	
Horn Coverage (H x V)	70° x 70°	
Enclosure	Trapezoidal Shape, MDF WOOD Black Paint, Handle, metal grille, rubber feet	
Input connectors	Input with Combo / Link with XLR	
External Controls	Volume Control / Power ON Volume Control / Power ON with Green LED / Clip Limiter with Red LED / Ground Lift	
Input Impedance	30 K Ohm Balanced / 15K Ohm Unbalanced	
Preset	FOH / Monitor	
Input Sensitivity	Line - 6dBu	
Protection Low-High	Analog Limiter	
Indicator	Power / Clip	
Power Supply	115V-60Hz / 230V-50Hz Switch mode	
Dimension (HxWxD)	448 x 390 x 437 mm / 17.64" x 15.35" x 17.21"	488 x 442 x 469 mm / 19.21" x 17.4" x 18.47"
Weight	12.74 Kg / 28.09 lbs	15.54 Kg / 34.26 lbs

www.toppopro.com



WWW.SISTEMAMT.IT



supporto@musictechnology.it



+39 071 7926753