

Active Subwoofers



KS Active Subwoofer

4000W **138dB** **CE**
TOTAL SYSTEM - PROGRAM POWER APPROVED



Combo I/O



XLR-F Link

Ground
& Phase Switch



KS 15A SUB

3"
VOICE
COIL



KS 18A SUB

3"
VOICE
COIL



KS 218A SUB

3"
VOICE
COIL



WWW.SISTEMAMT.IT



supporto@musictechnology.it



+39 071 7926753

KS Active Subwoofers Technical Specifications



	KS 15A SUB	KS 18A SUB
System Type	Active subwoofer	Active subwoofer
Power Rating	2000W PROGRAM / 4000W PEAK	2000W PROGRAM / 4000W PEAK
Transducer Low	15" Woofer, 3" Sandwich Voice Coil with long excursion	18" Woofer, 3" Sandwich Voice Coil with long excursion
Max SPL	131dB Max.	134dB Max.
Active Crossover	BandPass type 12dB/oct.	BandPass type 12dB/oct.
Frequency Response (-6dB) Under analog processor	45Hz - 120Hz	40Hz - 120Hz
Input Connector	In-Left / Mono (COMBO) Right (XLR-F) / Out-Left / Mono Right (XLR-M) / Link-Left / Mono-Right (XLR-M) Balanced (15K Ohm)	
External Controls	Volume Control / Phase Switch / HPF-80Hz for L-R Satellite or By Pass / Power ON with Green LED / Clip Limiter with Red LED / Ground Lift	
Electronic Protections	Thermal / Convection-Fan / Overload / Lim. / Compressor	
Power Supply	110-120V~50/60Hz or 220-240V~50/60Hz Switch mode	
Enclosure Construction	Plywood cabinet, metal grille, rubber feet	
Mounting	One metal standard pole-mount	
Dimensions (HxWxD)	450 x 580 x 485 mm (17.72" x 22.84" x 19.1")	535 x 661 x 516 mm (21.06" x 26.02" x 20.32")
Net Weight	24.95 Kg / 55.01 lbs	31.94 Kg / 70.42 lbs
Volume	7.58 CFT	10.45 CFT

KS218A SUB

System Type	Active subwoofer
Power Rating	4000W PROGRAM / 8000W PEAK
Transducer Low	2 x 18" Woofer, 3" Sandwich Voice Coil with long excursion
Max SPL	138dB Max.
Active Crossover	BandPass type 12dB/oct.
Frequency Response (-6dB) Under analog processor	35Hz - 120Hz
Input Connector	In-Left / Mono (COMBO) Right (XLR-F) / Out-Left / Mono Right (XLR-M) / Link-Left / Mono-Right (XLR-M) Balanced (15K Ohm)
External Controls	Volume Control / Phase Switch / HPF-80Hz for L-R Satellite or By Pass / Power ON with Green LED / Clip Limiter with Red LED / Ground Lift
Electronic Protections	Thermal / Convection-Fan / Overload / Lim. / Compressor
Power Supply	110-120V~50/60Hz or 220-240V~50/60Hz Switch mode
Enclosure Construction	Plywood cabinet, metal grille, rubber feet
Mounting	One metal standard pole-mount
Dimensions (HxWxD)	353 x 519 x 1000 mm / 13.9" x 20.43" x 39.37"
Net Weight	46.64 Kg / 102.82 lbs
Volume	15.89 CFT

www.toppopro.com



WWW.SISTEMAMT.IT



supporto@musictechnology.it



+39 071 7926753