

HD Active Subwoofers



KS HD Subwoofers

4000W **130dB**

TOTAL SYSTEM - PROGRAM POWER



APPROVED

Combo I/O

3 DSP Modes



XLR-F I/O

Crossover Frequency
3 Low Pass Filter Modes
& Phase Switch



Scratch-Resistant Paint Process



MAXHED
POWER MODULE Optimum Headroom & SPL



KS HD15A SUB

3"

VOICE COIL



KS HD18A SUB

3"

VOICE COIL



WWW.SISTEMAMT.IT



supporto@musictechnology.it



+39 071 7926753

KS HD Subwoofers Technical Specifications



KS HD15A SUB

System Type	15" Active Vented Subwoofer
Power Rating	2000W Program / 4000W Peak
Transducer Low	15" Ferrite Woofer, 3" Voice Coil with Long Excursion
Frequency Response (-6dB)	45Hz - 120Hz
Max.SPL	129dB
DSP Presets Modes	BOOST / EXTENDED LF / NORMAL
Crossover Frequency	80Hz / 100Hz / 120Hz selectable
Electronic Protections	Overheat Protection / Short Circuit Protection / Digital Compressor
Cooling	Temperature-controlled fan
Connectors	Input: Left Mono (Combo) / Right (XLR-F), Output: Left Mono / Right (XLR-M)
External Controls	Volume Control / Phase Switch / Switch for EQ Mode Selector / Switch for LPF / Power ON with Green LED / Limiter with Red LED
Power Supply	100-240V ~50/60Hz
Enclosure Construction	Plywood Cabinet, Resistant Black Paint, Metal Grille with Foam, Rubber Feet, Double handles
Mounting	One Metal Standard Pole-Mount
Dimensions (WxHxD)	580 x 450 x 503 mm / 22.83" x 17.72" x 19.80"
Net Weight	25.2 Kg / 55.55 lbs

KS HD18A SUB

System Type	18" Active Vented Subwoofer
Power Rating	2000W Program / 4000W Peak
Transducer Low	18" Ferrite Woofer, 3" Voice Coil with Long Excursion
Frequency Response (-6dB)	40Hz - 120Hz
Max.SPL	130dB
DSP Presets Modes	BOOST / EXTENDED LF / NORMAL
Crossover Frequency	80Hz / 100Hz / 120Hz selectable
Electronic Protections	Overheat Protection / Short Circuit Protection / Digital Compressor
Cooling	Temperature-controlled fan
Connectors	Input: Left Mono (Combo) / Right (XLR-F), Output: Left Mono / Right (XLR-M)
External Controls	Volume Control / Phase Switch / Switch for EQ Mode Selector / Switch for LPF / Power ON with Green LED / Limiter with Red LED
Power Supply	100-240V ~50/60Hz
Enclosure Construction	Plywood Cabinet, Resistant Black Paint, Metal Grille with Foam, Rubber Feet, Double handles
Mounting	One Metal Standard Pole-Mount
Dimensions (WxHxD)	661 x 535 x 537 mm / 26.02" x 21.06" x 21.12"
Net Weight	31.0 Kg / 68.33 lbs

www.toppopro.com



WWW.SISTEMAMT.IT



supporto@musictechnology.it



+39 071 7926753