

Active Subwoofers



MAXX Series

1200W **125dB** **CE**
TOTAL SYSTEM - PEAK POWER APPROVED



MAXHEB
POWER MODULE Optimum Headroom & SPL

Hi-Def
COMPONENTS

Rigging
READY!



MAXX 10A

2.5"
VOICE COIL

MAXX 12A

2.5"
VOICE COIL

MAXX 15A

2.5"
VOICE COIL



WWW.SISTEMAMT.IT



supporto@musictechnology.it



+39 071 7926753

MAXX Series Active Subwoofers Technical Specifications



MAXX 10A SUB

System Type	10" Active Subwoofer Speaker Cabinet
Transducer Low	10" woofer - 2.5" voice coil with ventilation
Frequency Response	50Hz-120Hz (-6dB)
Active Crossover:	HPF 80Hz under analog processor
Max SPL	94dB / 121.8dB Max
Power Rating	600W PROGRAM / 1200W PEAK
Input Connector	L-R (COMBO / XLR-F) / L-R Link (2 - XLR - M) / L-R Output (2 - XLR - M) Balanced (15K Ohm)
Input Level	L-R Line Input 0dBu
External Controls	Volume Control / Power on with Green LED / Clip Limiter with RED LED / Ground Lift / Phase Switch / HPF 100Hz Bypass
Power Supply	110-120V / 220-240V 50/60Hz
Enclosure Construction	Painted Plywood cabinet / Black Metal Grille Protection / Rubber feet
Dimensions (HxWxD)	536 x 501 x 391 mm / 21.1" x 19.72" x 15.39"
Weight	17.16 Kg / 37.83 lbs

MAXX 12A SUB

System Type	12" Active Subwoofer Speaker Cabinet
Transducer Low	12" woofer - 2.5" voice coil with ventilation
Frequency Response	47Hz-125Hz (-6dB)
Active Crossover:	HPF 80Hz under analog processor
Max SPL	96dB / 123.8dB Max
Power Rating	600W PROGRAM / 1200W PEAK
Input Connector	L-R (COMBO / XLR-F) / L-R Link (2 - XLR - M) / L-R Output (2 - XLR - M) Balanced (15K Ohm)
Input Level	L-R Line Input 0dBu
External Controls	Volume Control / Power on with Green LED / Clip Limiter with RED LED / Ground Lift / Phase Switch / HPF 100Hz Bypass
Power Supply	110-120V / 220-240V 50/60Hz
Enclosure Construction	Painted Plywood cabinet / Black Metal Grille Protection / Rubber feet
Dimensions (HxWxD)	629 x 579 x 474 mm / 24.76" x 22.8" x 18.66"
Weight	24 Kg / 52.91 lbs

MAXX 15A SUB

System Type	15" Active Subwoofer Speaker Cabinet
Transducer Low	15" woofer - 2.5" voice coil with ventilation
Frequency Response	45Hz-125Hz (-6dB)
Active Crossover:	HPF 80Hz under analog processor
Max SPL	97dB / 124.8dB Max
Power Rating	600W PROGRAM / 1200W PEAK
Input Connector	L-R (COMBO / XLR-F) / L-R Link (2 - XLR - M) / L-R Output (2 - XLR - M) Balanced (15K Ohm)
Input Level	L-R Line Input 0dBu
External Controls	Volume Control / Power on with Green LED / Clip Limiter with RED LED / Ground Lift / Phase Switch / HPF 100Hz Bypass
Power Supply	110-120V / 220-240V 50/60Hz
Enclosure Construction	Painted Plywood cabinet / Black Metal Grille Protection / Rubber feet
Dimensions (HxWxD)	676 x 581 x 544 mm / 26.61" x 22.87" x 21.42"
Weight	26.57 Kg / 58.58 lbs

www.toppopro.com



WWW.SISTEMAMT.IT



supporto@musictechnology.it



+39 071 7926753