

Festoon 2 RGB

Festoon 2 RGB is a décor string lighting system that replicates the feel of vintage event lighting. Both the string and individual bulbs are IP54 rated for temporary outdoor use so the colorful warmth of this effect can benefit events indoors or outdoors. Festoon 2 RGB is completely pixel-mappable for ultimate show and programming creativity, and the built-in automated programs create complex looks in seconds.



Highlights

- Complete string lighting system improves any environment
- String and bulbs are IP54 rated for temporary outdoor use
- System expands up to 3 strings (60 bulbs) per controller
- Pixel-mappable for ultimate show and programming creativity
- Built in automated programs create complex looks in seconds
- Access non-DMX control in Standalone mode from the digital display or optional
- Fits best in the CHS-50 gear bag

Specifications

- DMX Channels: 3, 9, Pixel or Pixel+
- DMX Connectors: 3-pin XLR
- Light Source: 5 SMD LEDs (tri-color RGB) 0.1 W, (20 mA), 50,000 hours life expectancy (per bulb)
- Strobe Rate: 0 to 10 Hz
- PWM Frequency: 604 Hz
- Coverage Angle: 360°
- IP Rating: IP54
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: (20 Bulbs): 42 W, 0.3 A @ 120 V, 60 Hz
 - (40 Bulbs): 77 W, 0.7A @ 120 V, 60 Hz
 - (60 Bulbs): 107 W, 0.9A @ 120 V, 60 Hz
 - (20 Bulbs): 47 W, 0.2 A @ 230 V, 50 Hz
 - (40 Bulbs): 78 W, 0.3 A @ 230 V, 50 Hz
 - (60 Bulbs): 108 W, 0.5 A @ 230 V, 50 Hz
- Weight: (Controller): 3.6 lbs (1.4 kg)
- Size: (String): 590.5 x 2.4 x 5.2 in (15,000 x 60 x 133 mm)
 - (Controller): 7.25 x 8 x 2 in (184 x 203 x 49 mm)
- Approvals: CE
- Optional Controllers: IRC-6

What's Included

- Controller
- 20 RGB bulbs
- Extension cable (5 m)
- Power cord
- Quick Reference Guide