

LEDPAR200IP RGBALC



200W RGBALC PARLED

LEDPAR200IP RGBALC is a COB LED stage par in the outdoor product line. There are RGBWA-UV and RGBALC optional. The rich choice would give you more idea to apply it for stage & event. It is our tooling for the housing and lens. So we could make the best color mixing with the suitable optic design. You could choose 20degree or 50degree version. Both are very good wash effect. It include the rich modes like master/slave, sound, built-in problem, auto running, DMX. The very good performance would earn a lot of benefit for the users.



COB LED
Source



RGBWA-UV
Color



Silent
Operation



Control
Protocol



IP Rated
Waterproof



Double
Handle



Parameters and technical information

LED	ProLight PBMM-200F6L-N01AE 200W Power LED	Working temperature	-15° - 45°C
Power	200W	Housing Material	Die casting magnesium
Max. Lumen	3881 Lm	Housing Color	Black
Input Voltage	AC100-240V,50-60HZ	IP Grade	IP65
Drive Current	0.8A/1.6A	Weight	5.6 Kg
Beam Angle	12° - 20°	Dimensions	283 x 253 x 360mm
Dimming	0 - 100%		
Cooling	Fan cooling		
Control Protocol	DMX512		
DMX Channel	6/8/12CH		
Power Cable	Seetronic waterproof DMX in/out(5 pin),Seetronic waterproof Power in/out		
DMX Cable	5 Pin In and Out		
Function:	Auto Running, Built-in Program, DMX512, Master/Slave, Static Color		

Accessories



C Clamp



Flightcase