

# LEDZOOM1910IP



## 19x10W RGBW 5IN1 PARLED

LEDZOOM1910IP represents a new generation in the field of RGBW LED PAR with ZOOM, with IP65, ideal for working both indoors and outdoors; designed for rental companies, fixed or mobile installations and as an excellent solution in any type of environment thanks to its compact design and versatility with its extraordinary 5° to 60° zoom. Versatile concept suitable for both stage and architectural lighting, in large and medium-sized environments. The peculiar monocular optical system with plano-convex terminations enhances the 19 x 10W RGBW / FullColor LED Source through a reflection technique that implies that the colors are pre-mixed in optical channels.



LED Source



Motorized ZOOM



Silent Operation



IP Rated Waterproof



Double Handle

### Parameters and technical information

LED Source	19x10W
Voltage	AC100V, 240V, 60 / 50Hz
Zooming Range	5°-60°
Led Brand	TX/5060RGBW
Rated Life (hours)	50000
Color Mixing	RGBW
Channel No.	5/6/7/8/9/10/14
Data Protocol	DMX512
Display Function	LCD
Menu Setting Funct.	4 Keyswitches
DMX Input/output	XLR-3
Input Voltage Range	AC100-240V
Input Freq. Range	50Hz-60Hz
Rated Power	210W
Max Power (100V)	217W
Connection No.	4pcs@100V/9pcs@240V

Cooling	Fan Cooling
Material	Tensile Aluminum+Metal Plate
IP Grade	66
Ambient Temp.	-10 - +45 °C
Max Humidity	75%@25 °C
Standard Color	Black
IP Grade	IP66
Dimensions	371 x 303 x 274 mm
Weight	8Kg

### Accessories



C Clamp



Flightcase