

Intimidator Free Spot 60 ILS

- 100% TRUE wireless, battery-operated moving head spot with built-in D-FI transceiver
- Adjustable run times ensure the fixture will last the length of the event
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- ILS compatibility for use in the ILS ecosystem
- Project crisp gobos from nearly any distance with the motorized focus
- New home position allows for smoother programming
- 3-facet prism splits the beam and covers a larger area
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Extend the fixture's lifespan with the onboard charge and discharge protection circuitry
- Fits Best in the CHS-50 Carry Bag

Specifications

- DMX Channels: 8, 10, or 14
- DMX Connectors: 3-pin XLR
- Pan and Tilt: 540°/270°
- Pan and Tilt Ranges: 180°, 360°, 540° pan/90°, 180°, 234° tilt
- Colors: 8 + white, split colors, continuous scroll at variable speeds
- Gobos: 7 + open (6 metal + 1 glass), rotating, interchangeable, slot-n-lock, continuous scroll at variable speeds
- Gobo Size: 28 mm outside, 23.8 mm image, 1.1 mm max thickness
- Prism: 3-facet round static
- Light Source: 1 LED (cool white) 70 W, (4.8A), 50,000 hours life expectancy
- Strobe Rate: 0 to 23 Hz
- Zoom Range (manual): 13° to 19°
- Illuminance (13°) : 16,932 lux @ 2 m
- Illuminance (19°) : 9,424lux @ 2 m
- Run Time (adjustable): 4, 6, or 8 hrs
- Recharge Time: 6.75 hours
- Color Temperature: 15,000 K
- Max Unobstructed Distance: 600 ft (183 m)
- Operating Frequency: 2.412 to 2.484 GHz
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 110 W, 0.9 A @ 120 V, 60 Hz
- Power and Current: 107 W, 0.5 A @ 230 V, 50 Hz
- Bracket Mounting Hole: M12
- Approvals: CE, UKCA , RoHS , FCC



- Weight: 22 lb (9.9 kg)
- Size: 11.4 x 11.9 x 15.4 in (290 x 301 x 391 mm)
- Optional Controllers: RFC, RFC-XL

